









www.tvsxl.com

Toll-free: 1800 2091 100

FEATURES



POWERFUL 4-STROKE ENGINE



WIDER FRONT PLATFORM



COMFORTABLE BROAD SEAT



DETACHABLE REAR SEAT



KICKER ON THE RIGHT SIDE



EASY CENTER STAND

TECHNICAL SPECIFICATIONS

ENGINE	
Туре	

4-Stroke Single Cylinder

Displacement 99.7 cc

Bore x Stroke 51.0 mm x 48.8 mm

Max. Power 4.2 PS @ 6000 rpm

Max. Torque 6.3 Nm @ 3500 rpm

DRIVE

Clutch Centrifugal Wet Type
Primary Drive Single Speed Gear Box
Secondary Drive Roller Chain Drive

DIMENSIONS

Wheelbase 1215 mm

Fuel tank capacity 4 ltr (including 1.3 ltr reserve)

Tyre size (Front & Rear) 2.5 x 16 & 2.5 x 16

Brake drum (Front & Rear) 80 mm dia & 110 mm dia

ELECTRICALS

Ignition system Fly wheel magneto 12 V, 90 W @ 5000 rpm
Head lamp 12 V - 35/35 W
Tail lamp 12 V - 5 W
Break lamp 12 V - 21 W

12 V - 3.4 W

Horn 12 V - DC Type 2A

Indicator lamp 12 V - 10 W

SUSPENSION

Speedo lamp

Suspension Front Telescopic spring type hydraulic
Suspension Rear Swing arm with hydraulic shocks

WEIGHT

Dry unladen 75 kg Gross 210 kg

In keeping with its policy of continuous improvement, TVS Motor Company reserves the right to change the specifications and/or features without notice. Accessories shown may not be part of standard equipment.

AVAILABLE COLOURS



TVS MOTOR COMPANY LIMITED

P.B. No. 4, Harita, Hosur-635 109, Tamil Nadu, India.
Telephone: +91 (4344) 276780 Fax: +91 (4344) 277311/276878
www.tvsmotor.in

