

**2023 KX250**

Starting At Rs.7,99,000 (Ex-Showroom)

**GET ON-ROAD PRICE**[\(https://kawasaki-india.com/on-road-price-estimator/\)](https://kawasaki-india.com/on-road-price-estimator/)

\*Product pictures shown are for illustration purpose only.

\*Actual product may vary from the picture shown here.

\*Specification and pricing are subject to change.

**AVAILABLE COLOURS**
● LIME GREEN
**Engine & Transmission**

TYPE	Liquid-cooled, 4-stroke Single
DISPLACEMENT	249cc
BORE AND STROKE	78.0 x 52.2 mm
COMPRESSION RATIO	14.1:1
VALVE SYSTEM	DOHC, 4 valves
FUEL SYSTEM	Fuel injection: ø44 mm x 1
FUEL TYPE / MINIMUM OCTANE RATING	-
IGNITION	Digital DC-CDI
STARTING	Electric
LUBRICATION	Forced lubrication, semi-dry sump
TRANSMISSION	5 speed, return
MAXIMUM POWER	-
MAXIMUM POWER WITH RAM AIR	-
MAXIMUM TORQUE	-

**Dimensions & Chassis**

FRAME TYPE	Perimeter, aluminium
RAKE / TRAIL	27.1° / 118 mm
TYRE - FRONT	80/100-21 51M
TYRE - REAR	110/90-19 62M
WHEELBASE	1,485 mm
GROUND CLEARANCE	345 mm
SEAT HEIGHT	960 mm
CURB MASS	108 kg
FUEL CAPACITY	6.2 litres
OVERALL DIMENSIONS (L X W X H)	2,190 x 820 x 1,270 mm

**Brakes & Suspension**

**Brakes & Suspension**

FRONT / WHEEL TRAVEL	ø48 mm inverted telescopic fork with adjustable compression and rebound damping / 314 mm
REAR / WHEEL TRAVEL	New Uni Trak with adjustable dual-range (high/low-speed) compression damping, adjustable rebound damping and adjustable preload / 316 mm
BRAKE - FRONT	Single semi-floating ø270 mm petal disc
CALIPER - FRONT	Dual-piston
BRAKE - REAR	Single 240 mm petal disc
CALIPER - REAR	Single-piston