











Never lose your way again with **Turn-by-Turn Navigation.** Stay connected wherever you go with **Smartphone Connectivity.** Come to a halt without missing a beat with **Single Channel ABS.** Feel the difference on every ride with **XSENS technology** that delivers optimum levels of riding pleasure, comfort and fuel efficiency.

9:33

opo

ASENS WITH FI TECHNOLOGY

71366 km

1[] km

FULLY LOADED WITH INFORMATION

The Xtreme 200S 4V is equipped with a state-of-the-art Full Digital LCD Meter to help you stay on top of every ride.



Full Digital LCD Meter with Gear Indicator, Service Reminder and Trip Meter



SPECIFICATIONS: XTREME 200S 4V

	ITEM	SPECIFICATIONS
Dimensions	Overall length	2222 mm
	Overall width	850 mm
	Overall height	1258 mm
	Wheelbase	1410 mm
	Ground clearance	220 mm
	Kerb weight	158 kg
	Saddle height	825 mm
Frame	Frame type	Diamond type
	Front suspension	Telescopic Front Forks (dia 37) with anti friction busi
	Front cushion stroke, mm	190
	Rear suspension	Rectangular swingarm with mono shock
	Rear cushion stroke, mm	170
	Front tyre	90/90-21 M/C 54S
	Rear tyre	120/80-18 M/C 62S
	Front brake	Petal Disc Dia. 276 mm
	Rear brake	Petal Disc Dia. 220 mm
	Fuel tank capacity	13.0 Litres
	Caster angle	27°
	Trail length	114 mm
	Fork oil grade	1F OIL
	Fork oil capacity	353 cc (Per leg)
Engine	Туре	Oil cooled, 4-Stroke 4-Valve single cylinder OHC
	Maximum power	19.1 PS @ 8500 Revolution Per Minute
	Maximum torque	17.35 Nm @ 6500 Revolution Per Minute
	Bore and stroke	66.5 mm X 57.5 mm
	Displacement	199.6cc
	Compression ratio	10:01
Drive train	Clutch system	Multi-plate, wet type
	Transmission	5-speed constant mesh
	Starting	Self and Kick
	Battery capacity	12V- 6 Ah, ETZ-7 *MF Battery
Electricals	Headlamp	LED
	Position lamp	LED
	Tail/Stop lamp	LED
	Turn signal lamp	Bulb type
	Instrument cluster	Full digital LCD, with Bluetooth & Turn by Turn navigatio



Pictures shown are for illustration purpose only and may not be exact representation of the product. It is our endeavour to constantly improve the product. This could lead to change in product specifications without any notice. Accessories & Feature shown may not be part of standard fitment. Actual colour of the vehicle may differ from those shown in the picture.

Hero MotoCorp Ltd. Regd. Office:

The Grand Plaza, Plot No. 2, Nelson Mandela Road, Vasant Kunj - Phase -II, New Delhi -110070, India.

CIN: L35911DL1984PLC017354 |

PAN: AAACH0812J

Phone No.: 011-46044100,

Fax No.: 011-26143198, 26143321. Toll Free No.: 1800-266-0018, Website: www.heromotocorp.com