Kawasaki

2024 KLX230RS

Starting At Rs.5,21,000 (Ex-Showroom)

*Product pictures shown are for illustration purpose only.

*Actual product may vary from the picture shown here.

*Specification and pricing are subject to change.



AVAILABLE COLOURS

LIME GREEN

Engine & Transmission	
ТҮРЕ	4st, 1-cyl, SOHC, 2val, Air-cooled
DISPLACEMENT	233 cm3
BORE AND STROKE	67.0 x 66.0 mm
COMPRESSION RATIO	9.4:1
VALVE SYSTEM	-
FUEL SYSTEM	Fuel injection (φ32 mm)
FUEL TYPE / MINIMUM OCTANE RATING	-
IGNITION	B&C (TCBI EL. ADV. D.)
STARTING	EL. Starter
LUBRICATION	Forced Lub. Wet
TRANSMISSION	6-speed, return
MAXIMUM POWER	14.6 kW {20 PS} / 8,000 RPM
MAXIMUM POWER WITH RAM AIR	-
MAXIMUM TORQUE	20.6 Nm {2.1 kg/m} / 6,000 RPM
ELECTRONIC RIDER AID	-
Dimensions & Chassis	
FRAME TYPE	Tubular, semi-double cradle
RAKE / TRAIL	27° / 108mm
TYRE - FRONT	80/100-21 51M
TYRE - REAR	100/100-18 59M
WHEELBASE	1,350 mm
GROUND CLEARANCE	275 mm
SEAT HEIGHT	900 mm
CURB MASS	115 kg
FUEL CAPACITY	6.6 Litres
OVERALL DIMENSIONS (L X W X H)	2035 x 840 x 1175mm
Brakes & Suspension	
FRONT / WHEEL TRAVEL	Telescopic fork / 220 mm
REAR / WHEEL TRAVEL	New Uni Trak Swingarm / 223 mm
BRAKE - FRONT	Single disc 213mm

Brakes & Suspension	
CALIPER - FRONT	-
BRAKE - REAR	Single disc 186mm
CALIPER - REAR	-