

2024 Z H2 EURO 5

Starting At Rs.23,48,000 (Ex-Showroom)

GET ON-ROAD PRICE[\(https://kawasaki-india.com/on-road-price-estimator/\)](https://kawasaki-india.com/on-road-price-estimator/)

*Product pictures shown are for illustration purpose only.

**AVAILABLE COLOURS**

● Metallic Carbon Gray/
Ebony

*Actual product may vary from the picture shown here.

*Specification and pricing are subject to change.

Engine & Transmission

TYPE	Liquid-cooled, 4-stroke In-Line Four with Supercharger
DISPLACEMENT	998 cm ³
BORE AND STROKE	76 x 55 mm
COMPRESSION RATIO	11.2:1
VALVE SYSTEM	DOHC, 16 valves
FUEL SYSTEM	Fuel injection: Ø40 mm x 4
FUEL TYPE / MINIMUM OCTANE RATING	Unleaded petrol/RON91
IGNITION	B&C (TCBI EL.ADV. D)
STARTING	Electric
LUBRICATION	Forced lubrication wet
TRANSMISSION	6-speed, return
MAXIMUM POWER	147.1 kW {200 PS} / 11,000 rpm
MAXIMUM POWER WITH RAM AIR	-
MAXIMUM TORQUE	137 N•m {14 kgf•m} / 8,500 rpm
ELECTRONIC RIDER AID	

Dimensions & Chassis

FRAME TYPE	Trellis, high-tensile steel
RAKE / TRAIL	24.9° / 104 mm
TYRE - FRONT	120/70ZR17M/C (58W)
TYRE - REAR	190/55ZR17M/C (75W)
WHEELBASE	1,455 mm

Dimensions & Chassis

GROUND CLEARANCE	140 mm
SEAT HEIGHT	830 mm
CURB MASS	239 kg
FUEL CAPACITY	19 litres
OVERALL DIMENSIONS (L X W X H)	2,085 x 810 x 1,130 mm

Brakes & Suspension

FRONT / WHEEL TRAVEL	Showa SFF-BP Fork with Adjustable Compression and Rebound Damping, Spring Preload Adjustability / 120mm
REAR / WHEEL TRAVEL	New Uni-Trak, Showa Gas-Charged Shock with Adjustable Compression and Rebound Damping, Preload Adjustability / 134mm
BRAKE - FRONT	Dual semi-floating ø320 mm discs,
CALIPER - FRONT	Dual radial - mount Brembo M4.32 monobloc, opposed 4-piston
BRAKE - REAR	Single ø260 mm disc
CALIPER - REAR	Single-piston