

2024 Z900 EURO 5

Starting At Rs.9,29,000 (Ex-Showroom)

GET ON-ROAD PRICE[\(https://kawasaki-india.com/on-road-price-estimator/\)](https://kawasaki-india.com/on-road-price-estimator/)

*Product pictures shown are for illustration purpose only.

**AVAILABLE COLOURS**

 Metallic Spark Black/Metallic Matt Dark Gray

 Ebony / Metallic Matte Graphene steel Gray

*Actual product may vary from the picture shown here.

*Specification and pricing are subject to change.

Engine & Transmission

TYPE	Liquid-cooled, 4-stroke In-Line Four
DISPLACEMENT	948 cc
BORE AND STROKE	73.4 x 56.0 mm
COMPRESSION RATIO	11.8:1
VALVE SYSTEM	DOHC, 16 valves
FUEL SYSTEM	Fuel injection:ø36 mm x 4 with sub-throttles
FUEL TYPE / MINIMUM OCTANE RATING	Unleaded Petrol/RON 95 Plus
IGNITION	Digital
STARTING	Electric
LUBRICATION	Forced lubrication, wet sump
TRANSMISSION	6-speed, return
MAXIMUM POWER	92.2 kW {125 PS} / 9,500rpm
MAXIMUM POWER WITH RAM AIR	--
MAXIMUM TORQUE	98.6 N.m {10.0 kgf.m} / 7,700 rpm
ELECTRONIC RIDER AID	

Dimensions & Chassis

FRAME TYPE	Trellis, high-tensile steel
RAKE / TRAIL	24.9° / 110 mm
TYRE - FRONT	120/70ZR17M/C (58W)
TYRE - REAR	180/55ZR17M/C (73W)

Dimensions & Chassis

WHEELBASE	1,455 mm
GROUND CLEARANCE	145 mm
SEAT HEIGHT	820 mm
CURB MASS	212 kg
FUEL CAPACITY	17 litres
OVERALL DIMENSIONS (L X W X H)	2,070 mm x 825 mm x 1,080 mm

Brakes & Suspension

FRONT / WHEEL TRAVEL	ø41 mm inverted fork with rebound damping and spring preload adjustability/120 mm
REAR / WHEEL TRAVEL	Horizontal Back-link with rebound damping and spring preload adjustability/140 mm
BRAKE - FRONT	Dual semi-floating ø300 mm petal discs
CALIPER - FRONT	Dual opposed 4-piston
BRAKE - REAR	Single ø250 mm petal disc
CALIPER - REAR	Single-piston